

Max. Gross Machine Weight 91,000 kg
Net Machine Weight 31,000 kg
Payload 60,000 kg
Engine YC6K520
Rated Power 382kW (512 hp / 519 ps) @ 1,900 rpm
Struck Capacity 26 m³
Heaped Capacity (SAE 2:1) 32 m³

DW90A MINING TRUCK

DW90A SPECIFICATIONS >>>

ENGINE	
Emission Regulation	Tier 3 / Stage III
Manufaturer	Yuchai
Model	YC6K520-GT30
Rated Power	382 kW (512 hp / 519 ps) @ 1,900 rpm
Peak Torque	2,400 N·m /1,100-1,500 rpm
Displacement	12.939 L
Number of Cylinders	6

TRANSMISSION	
Model	Allison 4800
Max. Speed	36 km/h
Retarder Model	Hydraulic Retarder

AXLE	
Front Axle Rated Load	20,000 kg
Rear Axle Rated Load	35,000*2 kg
Suspension Form	Leaf Spring
Max. Traction Force	320 kN
Max. Gradeability	≥32%

BRAKING	
Service Brake	Double Loop
Auxiliary Brake	Engine In-cylinder Brake
Service Braking Gradeability (load)	>38%
Park Braking Gradeability (load)	>19%
Pressure	1 Mpa
Air Tank Capacity	210 L

STEERING	
Steering System	Full Hydraulic Steering
System Pressure	16 MPa
Turn Radius	≤11,000 mm

HOIST SYSTEM	
Raise Time	≤ 21 s
Lower Time	≤ 21 s
System Pressure	22 MPa

DIMENSIONS OF THE WEDGE TAIL TYPE	
Body Lnner Size	6,500 mm*3,200 mm*1,450 mm
Struck Capacity	26 m ³
Heaped Capacity	32 m ³

TIRE AND RIM	
Drive Type	6x4
Tire	14.00R25
Rim	10.0/2.0-25

DIMENSIONS	
Overall Length	9,370 mm
Overall Width	3,575 mm
Overall Height	3,900 mm
Loading Height	3,470 mm
Wheel Base	3,800 mm+1,500 mm
Wheel Tread	2,765 mm + 2,525 mm
Min. Ground clearance	380 mm
Thickness Of Floor Plate	18 mm
Thickness Of Side Plate	10/12 mm





