

Max. Gross Machine Weight 105,000 kg
Net Machine Weight 36,000 kg
Payload 70,000 kg
Engine YC6K520
Rated Power 382 kW (512 hp / 520 ps) @ 1,900 rpm
Struck Capacity 36 m³
Heaped Capacity (SAE 2:1) 43 m³

## DW105A MINING TRUCK

## DW105A SPECIFICATIONS >>>

ENGINE	
Emission Regulation	Tier 3 / Stage III
Manufaturer	Yuchai
Model	YC6K520-GT30
Rated Power	382 kW (512 hp / 520 ps) @ 1,900 rpm
Peak Torque	2,400 N·m /1,100-1,500 rpm
Displacement	12.939 L
Number of Cylinders	6

TRANSMISSION	
Model	FAST 8DS240A
Max. Speed	30.9 km/h
Retarder Model	Hydraulic Retarder

AXLE	
Front Axle Rated Load	25,000 kg
Rear Axle Rated Load	40,000 x 2 kg
Suspension Form	Hydro-pneumatic Suspension
Total Reduction Ratio	16.641
Max. Gradeability	≥35%

BRAKING	
Service Brake	Double Loop
Auxiliary Brake	Engine In-cylinder Brake
Service Braking Gradeability (load)	>20%
Park Braking Gradeability (load)	>15%
Pressure	1 Mpa
Air Tank Capacity	210 L

STEERING	
Steering System	Full Hydraulic Steering
System Pressure	16 MPa
Turn Radius	≤12,000 mm

HOIST SYSTEM	
Raise Time	≤ 23 s
Lower Time	≤ 22 s
System Pressure	23 MPa

DIMENSIONS OF THE WEDGE TAIL TYPE	
Body Size	6,876 mm x 3,440 mm x 1,750 mm
Rotate Angle	48°
Struck Capacity	36 m <sup>3</sup>
Heaped Capacity	43 m <sup>3</sup>

TIRE AND RIM	
Drive Type	6x4
Tire Size	16.00R25
Rim	11.25/2.0-25

DIMENSIONS	
Overall Length	10,080 mm
Overall Width	3,620 mm
Overall Height	4,010 mm
Loading Height	3,590 mm
Wheel Base	3,950 mm + 1,750 mm
Wheel Tread	2,720 mm + 2,630 mm
Min. Ground clearance	400 mm
Fuel Tank Capacity	600 L





